

**EU type examination certificate**  
**EU-Baumusterprüfbescheinigung**

**CE-0085BT0055**

Product Identification No.  
Produkt-Identnummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Ali Group S.r.l. Via Gobetti, 2a, I-20063 Cernusco sul Naviglio (MI)
<b>Distributor</b> <i>Vertreiber</i>	MARENO Ali Group S.r.l. Via Conti Agosti, 231/247, I-31010 Mareno Di Piave (TV)
<b>Product Category</b> <i>Produktart</i>	Catering appliances: Boiling pan (2107)
<b>Product Description</b> <i>Produktbezeichnung</i>	Boiling pan
<b>Model</b> <i>Modell</i>	NPD...; NPI...; MNP...; MNPI...
<b>Countries of Destination</b> <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
<b>Test Reports</b> <i>Prüfberichte</i>	supplement test: 3402 A1 18 from 22.05.2019 (ING) type testing: 603/4917/1508 from 05.02.2018 (FGL)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 203-1 (01.07.2014) DIN EN 203-2/3 (01.04.2015)
<b>Date of Expiry / File No.</b> <i>Ablaufdatum / AZ</i>	19.03.2028 / 18-0911-GEA

70028-04-A-DE

11.09.2019 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-01

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Appliance Categories</b> <i>Gerätekategorien</i>	<b>Supply Pressures</b> <i>Versorgungsdrücke</i>	<b>Countries of Destination</b> <i>Bestimmungsländer</i>	<b>Remarks</b> <i>Bemerkungen</i>
I2E	20 mbar	LU, PL	
I2EK	20/25 mbar	NL	
I2H	20 mbar	NO	
I3+	28-30/37 mbar	LU	
I3B/P	28-30 mbar	CY, MT, NL, NO	
I3B/P	37 mbar	PL	
II1a2H	8, 20 mbar	CH, IT	only types ...G5/G8
II2E+3+	20/25, 28-30/37 mbar	BE, FR	
II2EK3B/P	20/25, 30 mbar	NL	
II2ELL3B/P	20, 50 mbar	DE	
II2ELs3B/P	20,13, 37 mbar	PL	not for types ...76G...; ...96G...
II2H3+	20, 28-30/37 mbar	ES, GB, GR, IE, IT, PT, SK	
II2H3B/P	20, 28-30 mbar	CZ, DK, EE, FI, HR, LT, LV, RO, SE, SI, TR	
II2H3B/P	20, 50 mbar	AT, CH	
II2HS3B/P	25, 30 mbar	HU	
II2HS3B/P	25, 50 mbar	HU	
III1a2H3B/P	8, 20, 28-30 mbar	DK	only types ...G5/G8
III1ab2H3B/P	8, 20, 28-30 mbar	SE	only types ...G5/G8

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
NPD76G5; NPI76G5; MNPD76G5; MNPI76G5; NPD96G5; NPI96G5; MNPD96G5; MNPI96G5	nominal heat input (Hi): 10,5 respectively 10,0 (I2K) kW	
NPD78G8; MNPD78G8; NPI78G8; MNPI78G8	nominal heat input (Hi): 17,0 respectively 16,5 (I2K) kW	
NPD98G10(A); NPI98G10(A); MNPD98G10(A); MNPI98G10(A)	nominal heat input (Hi): 21,0 respectively 20,5 (I2K) kW	
NPD98G15(A); NPI98G14(A); MNPD98G15(A); MNPI98G14(A)	nominal heat input (Hi): 24,0 respectively 22,5 (I2K) kW	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
...G5	nominal capacity: 50 litre
...G8	nominal capacity: 80 litre
...G10	nominal capacity: 100 litre
...G14	nominal capacity: 135 litre
...G15	nominal capacity: 150 litre
...D...	direct heated
...I...	indirect heated
...A	autoclave
M...	modular design

### Hints of Utilization /Remarks

#### *Verwendungshinweise / Bemerkungen*

electrical data: 220-240 V AC, 50 Hz or 220V AC 60 Hz, 15 W (direct heated); 275 W (indirect heated)

flue types: A1, B11 or B21 (B21 only under extraction hoods with interlocking)

Additionally tested appliance categories, supply pressures and countries of destination:

BG: II2H3B/P (20, 28-30 mbar)